

PUB. NO.: 54-095183 [JP 54095183 A]
PUBLISHED: July 27, 1979 (19790727)
INVENTOR(s): ODATE MITSUO
APPLICANT(s): MITSUBISHI ELECTRIC CORP [000601] (A Japanese Company or Corporation), JP (Japan)
APPL NO.: 53-003125 [JP 783125]
FILED: January 13, 1978 (19780113)
INTL CLASS: [2] H01L-025/10
JAPIC CLASS: 42.2 (ELECTRONICS — Solid State Components)
JOURNAL: Section: E, Section No. 141, Vol. 03, No. 117, Pg. 127, September 29, 1979 (19790929)

ABSTRACT

PURPOSE: To reduce the distortion applied to an element when an electrode is brought into contact with the element by pressure, by interposing a powder metallic layer with a particle diameter below 2.μm.

CONSTITUTION: A powder layer 7 with approximately 0.5 mm thickness is generated on the capacity bottom face of base electrode 2 and case 3. Element 1 is put on layer 7 so that electrode 13b may be at the top. Insulating ring 5 is inserted to leading-out electrode 4, and plate spring 6 is inserted. After that, the pressure over three times as large as the spring force of plate spring 6 is applied to solidify layer 7; and after the plate spring is fixed by a protrusion, a device is completed by welding and connection. In this structure, since powder layer 7 becomes a pressure buffering materials and the warp of element 1 is not reformed, element 1 is prevented from being affected by the distortion to a Si substrate and cracking. The thermal resistance and forward voltage drop are reduced.

BEST AVAILABLE COPY

